

Technical data sheets-JACKETED GLASS TAPE V62J

JACKETED GLASS TAPE "V62J"

The tape "V62J" is a Glass Textile manufactured for the Glass Industry when the Para-Aramide or PBO Textiles cannot used.

In the furnaces with IR lamp heating we can't use Para-Aramide or PBO Textiles, because their life is very short (maybe some UV rays there are); in this case we can use the V62J Glass Tape.

The V62J Tape is a standard Insulation Textured Glass tape (thickness mm.2-3-5) jacketed with a thin (mm. 0,20) Glass fabric, with a surface very smooth, homogeneous and regular; the jacket is stuck (we can sew also).

The V62J Tape resists at IR and UV rays at high temperatures, it is soft, it doesn't give off fibres and it is not expensive; his resistance to cut is not good.

TECHNICAL AND SUPPLY DATA

linside	Textured Glass Tape, thickness mm. 2 or 3 or 5
Outside	Self-Adhesive (one side) Glass fabric, thickness mm. 0,20
Kind of Glue	Silicone
Sewing yarn (when required)	Cotton Inox reiforced
Colour	White
Available sizes	Thickness: from mm. 2 to mm. 5 Width : from mm. 20 to mm. 100
Package	Rolls of 25 m.
Working temperature	500/550 °C